DECLARATION OF PERFORMANCE

No 202-15

1. Unique identification code of the product-type: 83035L-20B

2. Intended use/es: LVT luxury vinyl tile flooring, for indoor residential use, manufactured by calendering extrusion process. The flooring is waterproof and not suitable for outdoor application. Equipped with permanent self-adhesive backing, it requires full glue-down installation onto smooth, flat indoor sub floors in dry interior environments.The product complies with the limits specified in the standard, it does not contain ingredients harmful to health in excess of the limits.

3. Manufacturer: Shandong Primex Import and Export Co., Ltd. Room 407,Building 1,No.2 Yong ping Road, Licang District,Qingdao City,Shandong China 266000.

4. Authorised representative: Milo Zoff Flooring Kft.

1149 Budapest, Egressy út 23-25.

5. System/s of AVCP: system 3

6a. Harmonised standard: EN 16511, EN 14041:2018, EN 13501-1, EN 717-1, EN 1389, Test report 201026015SHF-001, 201026015SHF-002, ITC 753501980/2021.

Notified body/ies: Intertek Testing Services Shenzhen Ltd. Shanghai Fengxian Branch.

6b. European Assessment Document: No. ITC 753501980/2021

Notified body/ies: Shenzhen Ltd. Shanghai Fengxian Branch.

7. Declared performance/s: Test item 3~12 were carried out by SGS-CSTC Standards Technical Services Co.,Ltd. Guangzhou Branch. 3.ND=Not Detected (<MDL)

Wear layer: 0.3mm
Dimension: 184.15x1219.2x2,5mm
Quantity/weight per box: 25db = 5.612892m2, 22kg
Quantity/weight per pallet: 63 boxes = 353.6122m2, 1406kg

Characteristics	Test type	Result
General description		
Wear layer thickness deviation	GB/T 34440-2017	0.3mm
Slip resistance	DIN 51130:2014	Angle: 15.6 Rating: R10
Peel strength	GB/T 119982.1-2015	3.5N above
Dimensional stability after exposure to heat	GB/T4085-2015	0.1mm
Hot and cold warping	GB/T 34440-2017	0.1mm
Vinyl chloride monomer	GB/T18586-2001	0.08mm
Dynamic Coefficient of Friction	EN13893:2002	0.48mm
Thermal Conductivity	EN 12667:2001 Heat Flow Meter Method	0.125W/(m·K)
Fire classification for burning behavior of flooring material	EN13501-1:2018 Clause9& EN ISO 9239-1:2010 &EN ISO11925-2:2020	B-s1
PBDEs	IEC 62321-6:2015	ND
Pentachlorophenol (PCP)	EN14041:2018 Annex B & EN 12673:1999	ND

扫描全能王
3亿人都在用的扫描App

Elementary Analysis	EN 1122:2001	ND
Formaldehyde	EN717-1:2004	ND
Phthalates	EN14041:2018 Annex F	ND
Chlorinated Paraffins	ISO18219:2015	ND
Flame resistance	EN 13501-01	Cfl-S1
Polycyclic Aromatic Hydrocarbons (PAHs)	EN 14041:2018 Annex E	ND
Organotin Compounds	ISO/TS 16179:2012	ND
Perfluorooctanoic acid (PFOA and its salts	CEN/TS15968:2010	ND

8. Appropriate Technical Documentation and/or Specific Technical Documentation:
Shenzhen Ltd. Shanghai Fengxian Branch.

The performance of the product identified above is in conformity with the set of declared performance/s. This de claration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Shandong Primex Import and Export Co., Ltd. Room 407,Building 1,No.2 Yong ping Road, Licang District,Qingdao City,Shandong China 266000.
[name] .....

At [place] .....on [date of issue] .....

[signature] .....

扫描全能王
3亿人都在用的扫描App